

FLASH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : FLASH
Product code : H1640

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : CONCRETE CLEANER

1.3. Details of the supplier of the safety data sheet

CleanPak Products LLC.
221 Hobbs Street Suite 108
Tampa, FL 33619
T 813-740-8611 - F 813-740-8218
admin@cleanpakproducts.com - www.cleanpakproducts.com

1.4. Emergency telephone number

Emergency number : 1-800-535-5053
InfoTrac

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Corr. 1A H314
Aquatic Acute 3 H402

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS05

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H314 - Causes severe skin burns and eye damage
H402 - Harmful to aquatic life

Precautionary statements (GHS-US) :

P260 - Do not breathe dust
P264 - Wash hands, forearms and face thoroughly after handling
P280 - Wear gloves and protective eyewear
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

FLASH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixture

Name	Product identifier	%	GHS-US classification
disodium metasilicate	(CAS No) 6834-92-0	50 - 70	Skin Corr. 1A, H314
sodium carbonate	(CAS No) 497-19-8	20 - 30	Skin Corr. 1A, H314 Aquatic Acute 3, H402
trisodium orthophosphate	(CAS No) 7601-54-9	5 - 10	Skin Corr. 1A, H314

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove the victim into fresh air.
First-aid measures after skin contact : Rinse with water.
First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open.
First-aid measures after ingestion : Drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : EXTINGUISHING MEDIA FOR SURROUNDING FIRES:

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

For containment : Plug the leak, cut off the supply.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Maximum storage period : > 2 year
Storage area : Keep only in the original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

FLASH	
ACGIH	Not applicable

FLASH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

FLASH	
OSHA	Not applicable
sodium carbonate (497-19-8)	
ACGIH	Not applicable
OSHA	Not applicable
disodium metasilicate (6834-92-0)	
ACGIH	Not applicable
OSHA	Not applicable
trisodium orthophosphate (7601-54-9)	
ACGIH	Not applicable
OSHA	Not applicable

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: White to light yellow
Odour	: Characteristic odour
Odour threshold	: No data available
pH	: ≈ 12.5
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Specific gravity	: No data available
Solubility	: Soluble in water. Water: Solubility in water of component(s) of the mixture : • sodium carbonate: 22 g/100ml • disodium metasilicate: > 18 g/100ml • trisodium orthophosphate: 8 g/100ml (20 °C)
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

FLASH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong acids. Oxidizing agent.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

sodium carbonate (497-19-8)	
LD50 oral rat	2800 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Experimental value)
ATE US (oral)	2800.000 mg/kg bodyweight
disodium metasilicate (6834-92-0)	
LD50 dermal rat	> 5000 mg/kg bodyweight (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
trisodium orthophosphate (7601-54-9)	
LD50 oral rat	4800 mg/kg (Rat; OECD 420: Acute Oral toxicity – Acute Toxic Class Method; Experimental value; >2000 mg/kg bodyweight; Rat)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)
ATE US (oral)	4800.000 mg/kg bodyweight

Skin corrosion/irritation : Causes severe skin burns and eye damage.
pH: ≈ 12.5

Serious eye damage/irritation : Not classified
pH: ≈ 12.5

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

sodium carbonate (497-19-8)	
LC50 fishes 1	300 mg/l (96 h; Lepomis macrochirus)
EC50 Daphnia 1	< 424 mg/l (48 h; Daphnia magna)
EC50 other aquatic organisms 1	14 mg/l (168 h; Plankton)
LC50 fish 2	740 mg/l (96 h; Gambusia affinis)
EC50 Daphnia 2	265 mg/l (48 h; Daphnia magna)
TLM fish 1	300 ppm (96 h; Lepomis macrochirus)
TLM other aquatic organisms 1	500 ppm (96 h; Daphnia magna)
Threshold limit algae 1	242 mg/l (5 days; Algae)
disodium metasilicate (6834-92-0)	
LC50 fishes 1	210 mg/l (96 h; Brachydanio rerio)
EC50 Daphnia 1	216 mg/l (96 h; Daphnia magna; GLP)
LC50 fish 2	2320 mg/l (96 h; Gambusia affinis)

FLASH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

sodium carbonate (497-19-8)	
EC50 Daphnia 2	632 mg/l (96 h; Lymnaea sp.)
Threshold limit algae 1	207 mg/l (72 h; Scenedesmus subspicatus; GLP)
trisodium orthophosphate (7601-54-9)	
LC50 fishes 1	2400 mg/l (48 h; Leuciscus idus)
LC50 fish 2	220 mg/l (96 h; Lepomis macrochirus)

12.2. Persistence and degradability

sodium carbonate (497-19-8)	
Persistence and degradability	Biodegradability: not applicable. Low potential for adsorption in soil.
ThOD	Not applicable (inorganic)
disodium metasilicate (6834-92-0)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
trisodium orthophosphate (7601-54-9)	
Persistence and degradability	Biodegradability: not applicable. Biodegradability in soil: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

sodium carbonate (497-19-8)	
Log Pow	-6.19 (Estimated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
disodium metasilicate (6834-92-0)	
Bioaccumulative potential	Bioaccumulation: not applicable.
trisodium orthophosphate (7601-54-9)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer :
Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : May be discharged to wastewater treatment installation.

SECTION 14: Transport information

In accordance with DOT
Transport document description : UN3253 Disodium trioxosilicate, 8, III
UN-No.(DOT) : UN3253
Proper Shipping Name (DOT) : Disodium trioxosilicate
Department of Transportation (DOT) Hazard Classes : 8 - Class 8 - Corrosive material 49 CFR 173.136

FLASH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : III - Minor Danger

DOT Special Provisions (49 CFR 172.102) : IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2).

IP3 - Flexible IBCs must be sift-proof and water-resistant or must be fitted with a sift-proof and water-resistant liner.

T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)

TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Packaging Non Bulk (49 CFR 173.xxx) : 213

DOT Packaging Bulk (49 CFR 173.xxx) : 240

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 25 kg

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 100 kg

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 52 - Stow "separated from" acids

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : 3253

Proper Shipping Name (IMDG) : DISODIUM TRIOXOSILICATE

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : III - substances presenting low danger

Air transport

UN-No.(IATA) : 3253

Proper Shipping Name (IATA) : DISODIUM TRIOXOSILICATE

Class (IATA) : 8 - Corrosives

Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

CANADA

FLASH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

No additional information available

15.3. US State regulations

SECTION 16: Other information

Full text of H-phrases:

Aquatic Acute 3	Hazardous to the aquatic environment — Acute Hazard, Category 3
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
H314	Causes severe skin burns and eye damage
H402	Harmful to aquatic life

HMIS III Rating

Health : 0 Minimal Hazard - No significant risk to health

Flammability : 0 Minimal Hazard

Physical : 0 Minimal Hazard

Personal Protection : B

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product