

Premium Alkaline Tile and Grout Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 12/31/2014

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Premium Alkaline Tile and Grout Cleaner
Product code : P194

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Tile and Grout cleaner

1.3. Details of the supplier of the safety data sheet

CleanPak Products LLC.
221 Hobbs Street Suite 108
Tampa, FL 33619
T 813-740-8611 - F 813-740-8218
admin@cleanpakproducts.com - www.cleanpakproducts.com

1.4. Emergency telephone number

Emergency number : 1-800-535-5053
InfoTrac

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Corr. 1A H314

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS05

Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : H314 - Causes severe skin burns and eye damage
Precautionary statements (GHS-US) : P280 - Wear gloves and protective eyewear
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a physician
P363 - Wash contaminated clothing before reuse

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Premium Alkaline Tile and Grout Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
sodium hydroxide	(CAS No) 1310-73-2	10 - 12	Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314 Aquatic Acute 3, H402
disodium metasilicate	(CAS No) 6834-92-0	1 - 5	Skin Corr. 1A, H314

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Soap may be used. Rinse skin with water/shower.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- First-aid measures after ingestion : Give milk to drink.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Coughing.
- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray.

5.2. Special hazards arising from the substance or mixture

- Reactivity : May be corrosive to metals. Reacts violently with (strong) acids.

5.3. Advice for firefighters

No additional information available

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Corrosion-proof appliances.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Stop leak if safe to do so.

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill.
- Methods for cleaning up : Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Observe strict hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container closed when not in use. Store in original container.
- Incompatible products : Oxidizing agent. Strong acids.

Premium Alkaline Tile and Grout Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Maximum storage period : >= 2 year

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Premium Alkaline Tile and Grout Cleaner		
ACGIH	Not applicable	
OSHA	Not applicable	
sodium hydroxide (1310-73-2)		
ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³
OSHA	Not applicable	
disodium metasilicate (6834-92-0)		
ACGIH	Not applicable	
OSHA	Not applicable	

8.2. Exposure controls

Hand protection : Gloves.

Eye protection : Safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Colorless watery liquid.

Colour : Colourless

Odour : No data available

Odour threshold : No data available

pH : 13 - 14

pH solution : 10

Relative evaporation rate (butylacetate=1) : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : >= 100 °C

Flash point : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : No data available

Vapour pressure : No data available

Relative vapour density at 20 °C : No data available

Specific gravity : 1.06 (≥ 1.06)

Solubility : Soluble in water.
Water: 100

Log Pow : No data available

Log Kow : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive properties : No data available

Oxidising properties : No data available

Explosive limits : No data available

Premium Alkaline Tile and Grout Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

May be corrosive to metals. Reacts violently with (strong) acids.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong acids. May be corrosive to metals.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

sodium hydroxide (1310-73-2)	
LD50 dermal rabbit	1350 mg/kg (Rabbit; Literature)
ATE US (dermal)	1350.000 mg/kg bodyweight
disodium metasilicate (6834-92-0)	
LD50 dermal rat	> 5000 mg/kg bodyweight (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: 13 - 14
Serious eye damage/irritation	: Not classified pH: 13 - 14
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity (single exposure)	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity (repeated exposure)	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Symptoms/injuries after inhalation	: Coughing.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Dangerous for the environment.

Premium Alkaline Tile and Grout Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

sodium hydroxide (1310-73-2)	
LC50 fishes 1	45.4 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); Solution >=50%)
EC50 Daphnia 1	40.4 mg/l (48 h; Ceriodaphnia sp.; Nominal concentration)
LC50 fish 2	189 mg/l (48 h; Leuciscus idus)
TLM fish 1	99 mg/l (48 h; Lepomis macrochirus)
TLM fish 2	125 ppm (96 h; Gambusia affinis)
disodium metasilicate (6834-92-0)	
LC50 fishes 1	210 mg/l (96 h; Brachydanio rerio)
EC50 Daphnia 1	216 mg/l (96 h; Daphnia magna; GLP)
LC50 fish 2	2320 mg/l (96 h; Gambusia affinis)
EC50 Daphnia 2	632 mg/l (96 h; Lymnaea sp.)
Threshold limit algae 1	207 mg/l (72 h; Scenedesmus subspicatus; GLP)

12.2. Persistence and degradability

Premium Alkaline Tile and Grout Cleaner / King Cobra	
Persistence and degradability	Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
sodium hydroxide (1310-73-2)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
disodium metasilicate (6834-92-0)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

sodium hydroxide (1310-73-2)	
Bioaccumulative potential	Bioaccumulation: not applicable.
disodium metasilicate (6834-92-0)	
Bioaccumulative potential	Bioaccumulation: not applicable.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer	:
Effect on the global warming	: No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Neutralize.
Additional information	: Clean up even minor leaks or spills if possible without unnecessary risk.

SECTION 14: Transport information

In accordance with DOT	
Transport document description	: UN1824 Sodium hydroxide solution, 8, III
UN-No.(DOT)	: UN1824
Proper Shipping Name (DOT)	: Sodium hydroxide solution
Department of Transportation (DOT) Hazard Classes	: 8 - Class 8 - Corrosive material 49 CFR 173.136

Premium Alkaline Tile and Grout Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : III - Minor Danger

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

N34 - Aluminum construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material.

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154 Limited Quantity

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 52 - Stow "separated from" acids

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : 1824

Proper Shipping Name (IMDG) : SODIUM HYDROXIDE SOLUTION

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : III - substances presenting low danger

Air transport

UN-No.(IATA) : 1824

Proper Shipping Name (IATA) : SODIUM HYDROXIDE SOLUTION

Class (IATA) : 8 - Corrosives

Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

CANADA

EU-Regulations

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

Premium Alkaline Tile and Grout Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2.2. National regulations
No additional information available

15.3. US State regulations

SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Aquatic Acute 3	Hazardous to the aquatic environment — Acute Hazard, Category 3
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H402	Harmful to aquatic life

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product