

P158

DEFOAMER PLUS

CONCENTRATED FOAM REDUCER

DESCRIPTION:

Emulsified silicone dimethyl siloxane scientifically breaks down the surface tension on detergents.

DIRECTIONS:

Shake or stir before using.

Carpet steam extractors: As a starting point, add one ounce of chemical to ten gallons of waste solution tank capacity. Unusual jobs may require a second application.

Automatic floor scrubbers: For foaming problems in waste solution tanks, add 1-2 ounces of chemical per 10 gallons of water solution tank capacity.

Sewage and industrial water: The composition of these fluids may vary widely. It is suggested that a concentration of 10 ounces per 500 gallons can be used as starting point and that this concentration be varied up or down until effective control is achieved. Add chemical up stream to allow maximum mixing action before the foam generation point is reached.

PHYSICAL PROPERTIES

APPEARANCE: Milky white liquid

Specific Gravity: 1 .0

Odor: Aromatic

pH: 5-7

Solubility in water:: Soluable

PACKAGING

Stocked in quarts and gallons.

Other sizes available.
Call for minimums

CleanPak Products LLC.

221 Hobbs St. Suite 108

Tampa, FL 33619

T 813-740-8611 - F 813-740-8218

www.cleanpakproducts.com