

P523

SUN SEAL

Water-based brick and concrete sealer. Designed for interior and exterior applications. Low Odor----Non-Flammable----Weatherproof. Color Enhancer Non-yellowing. No Acid Etching required

DESCRIPTION:

SUN SEAL is a water based interior and exterior brick and concrete seal. SUN SEAL is a non-yellowing and UV resistant coating. SUN SEAL will add color and gloss to brick and stone. SUN SEAL has low sensitivity to amine based strippers and cleaners, making for an easily cleaned surface. When using SUN SEAL as a curing compound it helps control hydration of the cement by preventing rapid moisture loss from the surface of newly placed cement.

DIRECTIONS:

Always pretest for compatibility in a small inconspicuous area. Area to be sealed must be clean and free of dust, dirt, grease, oil, rust and efflorescence. SUN SEAL may be applied by airless sprayer, pump-up sprayer, mop, roller, or lambs wool applicator. For concrete apply 2 coats allowing 2 hour dry time between coats. If a higher gloss is desired apply 1 to 2 more coats of SUN SEAL. Coverage rates for concrete are approximately 500 to 1500 ft² per gallon depending upon porosity of the concrete. To use SUN SEAL as a membrane curing compound apply at 200 ft² per gallon.

For exterior brick apply 1 to 2 coats of SUN SEAL allowing 2 hour dry time between coats. Apply to brick at a coverage rate of 500 ft² per gallon.

PRECAUTIONARY STATEMENTS:

Wear gloves and protective eyewear. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations.

PHYSICAL PROPERTIES

APPEARANCE: Milky White Liquid

Specific Gravity: 1 .055

Odor: Characteristic

pH: 8-8.5

Solubility in water:: n/a

PACKAGING

Stocked in gallons and pails.

Other sizes available.
Call for minimums

CleanPak Products LLC.

221 Hobbs St. Suite 108

Tampa, FL 33619

T 813-740-8611 - F 813-740-8218

www.cleanpakproducts.com