

P626

ARC
**ACID REPLACEMENT
CONCENTRATE**



DIRECTIONS:

Use on porcelain tile and metal to remove soap scum and general bathroom grime. It will not harm metals.

CONCRETE CLEANING: Dilute 1 part ARC with three parts water. Use a brush or pressure washer to gain agitation. **TILE AND GROUT:** Dilute 9 parts water and 1 part ARC. **GENERAL BATHROOM CLEANING:** Dilute 8 ounces of ARC in a gallon of water.

For general Industrial Descaling use undiluted. Process until clean, verifying the pH as under 5. If above add more ARC and continue until clean and solution is under 5.

PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Wear gloves and protective eyewear. If swallowed: Call a doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If on skin: Wash with plenty of water.



PHYSICAL PROPERTIES

APPEARANCE: Red liquid

Specific Gravity: 1.143

Odor: Almost odorless

pH: <2.0

Solubility in water:: Soluable

PACKAGING

Stocked in quarts and gallons.

Other sizes available.
Call for minimums

CleanPak Products LLC.

221 Hobbs St. Suite 108
Tampa, FL 33619
T 813-740-8611 - F 813-740-8218
admin@cleanpakproducts.com -
www.cleanpakproducts.com